

VITA System 12 Vertical Enclosure (10U)




FEATURES:

- 19" Rackmount fully compliant to Eurocard and IEEE standards
- 10U x 84HP x 20" (H x W x D)
- 6U vertical card mounting
- 2 to 21 slot VITA-Based System Platforms (VME, VME64x, VPX, VXS, VXI)
- Advanced EMC shielding to meet CE and FCC
- Cooling front to rear
- Wide range of PSU inputs (90 - 264 VAC, 48 VDC)
- Fixed-mount or front pluggable PSUs with redundant hot swap options
- System monitoring for DC voltages, fan fail and over temp (optional)
- Connector options: 3 Row (96 PIN), 5 Row (160 PIN), 5 Row + PO, RT-2
- Ready to run - turnkey solution


SCOPE OF SUPPLY

High quality 19" rackmount chassis platform consisting of alodined aluminum enclosures, high performance VITA System backplane, power supply, cooling system and AC/DC power components. Assembled, wired and tested prior to shipment.

ORDERING INFORMATION



Description	Order Number
<ul style="list-style-type: none"> ■ 17.5" (H) x 17" (W) x 19.68" (D) ■ Holds 12, 6U x 160mm Cards ■ 12 Slot VME or VME64x Backplane ■ 6 x 5.25" HH Devices ■ 2 x 114 CFM, 12V DC Fans ■ 500W: +5V/80A; +12V/10A; -12V/10A, or 600W: +5V/75A; +12V/12A; -12V/4A; 3.3V/40A 	12V12MMCA8N5VC51 VME
	12V12OPCA8N5VCF1 64X



Description	Order Number
<ul style="list-style-type: none"> ■ 17.5" (H) x 17" (W) x 19.68" (D) ■ Holds 21, 6U x 160mm Cards ■ 21 Slot VME or VME64x Backplane ■ 2 x 5.25" HH Devices ■ 3 x 150 CFM ■ 750W: 5V/120A; +12V/12A; -12V/10A, or 800W: 5V/120A; +12V/12A; -12V/10A; 3.3V/40A 	12V21MM4A8N5VC71 VME
	12V21OP4A8N5VCH1 64X

